



MC48 .../5 A

MC48 .../5 A, Amperímetre màxime bimetal·lic

Code: M12211. [CONSULTAR DISPONIBILIDAD](#)

- > Escala: 90°, P1, 2
- > Precisió: 3
- > Rang mesura (A): .../5 A
- > Mòduls: 48x48

Especificacions

Mechanical characteristics

Size (mm) width x height x depth	48 x 48 x 66.2 (mm)
Fastening	Panell
Weight (kg)	0,11

Environmental characteristics

Protection class	Panell: IP 52 (Frontal), IP 00 (Terminals)
Storage temperature	-25...+40 °C
Operating temperature	+10 ... +30 °C

Standards

Certifications	CE
Electrical safety, Maximum height (m)	2000
Standards	BS 89, UNE-EN 60051, IEC 144, DIN 43780, IEC 51, UNE 21318

Current measurement circuit

Consumption	3,25 VA
Allowable overload	1,5 In permanent / 15 In durant 1s

Electrical characteristics

Insulation voltage, circuit	2 KV A 50 HZ < 1min entre mecanismo y caja
-----------------------------	--

Measurement accuracy

Accuracy	± 3 % FE
----------	----------

MC
Amperímetres màximes

CODI	TIPUS	Escala	Precisió	Rang mesura (A)	Mòduls
M12211.	MC48 .../5 A	90°, P1, 2	3	.../5 A	48x48
M12221.	MC72 .../5A	90°, P1, 2	3	.../5 A	72x72
M15521.	MC72 .../5A 120%	90°, P1, 2	3	.../5 A	72x72
M12231.	MC96 .../5 A	90°, P1, 2	3	.../5 A	96x96
M15531.	MC96 .../5A 120%	90°, P1, 2	3	.../5 A	96x96



MC48 .../5 A

Code: M12211.

CODI	TIPUS	Escala	Precisió	Rang mesura (A)	Mòdul
M12241.	MC144 .../ 5A	90°, P1, 2	3	.../5 A	144x144

Scale NOT included



MC48 .../5 A

Code: M12211.

Conexions

