



EMC144 .../5A

EMC144 .../5A, Amperímetre màxímetre bimetàl·lic + amperímetre ferro mòbil, panell 144x144

Code: M12642. **DESCATALOGADO**

- > Escala: Doble escala 90°, P1,2, ferro mòbil P2
- > Precisió: Bimetàl·lic: 3 Ferro mòbil:1,5
- > Rang mesura (A): .../5 A
- > Mòduls: 144x144

Descripció

- No necessiten alimentació auxiliar
- Caixes DIN de dimensions 48, 72, 96 i 144 mm.
- Classe de precisió 3
- Mesura a C.A. de .../5 A (sota demanda .../1 A)
- Escales intercanvials per a MC48, MC72, MC96, MM 45, EMC72, EMC96
- Temps d'inèrcia tèrmica de 15 min (sota demanda, 8 i 30 min)

Aplicació

Per controlar en un mateix equip l'estat del corrent altern i mesurar sobrecàrregues de llarga durada, integrades en un període determinat.



EMC144 .../5A

Amperímetres màximes

Code: M12642.

Especificacions

Mechanical characteristics

Size (mm) width x height x depth	144 x 144 x 71.8 (mm)
Fastening	Panell
Weight (kg)	0,56

Environmental characteristics

Protection class	Panell: IP 52 (Frontal), IP 00 (Terminals)
Storage temperature	-25...+40 °C
Operating temperature	+10 ... +30 °C

Standards

Certifications	CE
Electrical safety, Maximum height (m)	2000
Standards	BS 89, UNE-EN 60051, IEC 144, DIN 43780, IEC 51, UNE 21318

Current measurement circuit

Consumption	4,25 VA
Allowable overload	1,5 In permanent / 15 In durant 1s

Electrical characteristics

Insulation voltage, circuit	2kV a 50 Hz < 1min entre mecanismo y caja
-----------------------------	---

Measurement accuracy

Accuracy	±3 % Bim. / ±1,5 % HM
----------	-----------------------

EMC

Amperímetres màximes

CODI	TIPUS	Escala	Precisió	Rang mesura (A)	Mòduls
M12622.	EMC72 .../5A	Doble escala 90°, P1,2, ferro mòbil P2	Bimetàl·lic	.../5 A	72x72
M12632.	EMC96 .../5A	Doble escala 90°, P1,2, ferro mòbil P2	Bimetàl·lic	.../5 A	96x96
M12642.	EMC144 .../5A	Doble escala 90°, P1,2, ferro mòbil P2	Bimetàl·lic	.../5 A	144x144
M12651.	MMC45 .../5A	90°, P1, 2	3	.../5 A	
M12661.	MMCSC45 .../5A	90°, P1, 2	3	.../5 A	

Scale NOT included



EMC144 .../5A

Amperímetres màxims

Code: M12642.

Conexions

