

LR 04-017

LR 04-017, Reactància de filtre per a Convertidor de potència (costat xarxa)

Code: P70307. DESCATALOGADO

- > L(mH): 1,85
- > In (A): 17
- > Pèrdues: 25
- > P. motor: 7.5
- > P. motor (CV): 10

Especificacions

Mechanical characteristics

Size (mm) width x height x depth	150 x 150 x 75 (mm)
Envelope	Conductor type: copper wire
Weight (kg)	2,6

Environmental characteristics

Thermal Class	class F (+155 °C) On request: class H (+180 °C)
Protection class	IP 00
Installation, location, position.	Inside
Ambient temperature	-10 ... +45 °C

Electrical characteristics

Linearity (5% L)	1,5 In
Maximum transient current	2 In (1 min)
Voltage	Fins a 1000 Vca
Tolerance L	± 5 %
L value (mH)	1.85
Insulation voltage, circuit	4 kV

Current measurement circuit

Nominal current (In)	Segons taula. Sota demanda altres valors
Allowable overload	1,7 In
Permanent overload	1,7 In


Standards

Standards	UNE-EN 60289 , IEC 60076
-----------	--------------------------

LR-LRB

Reactància de filtre per a convertidor de potència (costat xarxa), 50 Hz.

CODI	TIPUS
P70301.	LR 04-003
P70302.	LR 04-004



LR 04-017

Code: P70307.

CODI	TIPUS
P70303.	LR 04-006
P70304.	LR 04-008
P70305.	LR 04-010
P70306.	LR 04-013
P70307.	LR 04-017
P70308.	LR 04-022
P70309.	LR 04-033
P7030B.	LR 04-050
P7030D.	LR 04-066
P7030E.	LRB 04-080
P7030G.	LRB 04-115
P7030J.	LRB 04-185
P7030K.	LRB 04-200
P7030M.	LRB 04-300