

eManager Pro Energy X2

eManager Pro Energy X2, ARM controller

Code: D302000080000 **DESCATALOGADO**

> Memory: 512 MB | 8 GB eMMC

> Módules: 7

> Communications: RS232/485 | Ethernet | Wi-Fi

> System: 2 xThree-phase / 6 xSingle-phase

> Power supply: 85 ... 264 V~

> CPU: ARM Cortex A7 800 MHz

Description

eManager Energy is an industrial IoT controllers product range with integrated three-phase energy metering. eManager Energy centralizes power network analyzer features with datalogging and communications.
The energy module is able to mesure up to one three-phase circuit or three single-phase circuits. It integrates 4 quadrant monitoring, including the main electrical parameters for single-phase and three-phase. Measurement accuracy is Class 1 Active and Class 2 Reactive; and the secondary current is 1 A.
In addition, a custom Node-RED node is available to facilitate the data collecting and displaying with a local real-time dashboard that can be accessed via their own Wi-Fi network.



eManager Pro Energy X2

Code: D302000080000

Specifications

AC power supply

Consumption	8,8 ... 10,5 VA
Frequency	47 ... 63 Hz
Nominal voltage	85 ... 264 V~

DC power supply

Consumption	6,4 ... 6,5 W
Nominal voltage	120 ... 300 Vdc

Electrical characteristics

Isolation level	3 kVac

Mechanical characteristics

Size (mm) width x height x depth	123 x 89 x 48 (mm)
Envelope	Polycarbonate UL94 - Self-extinguishing V2
Fastening	DIN rail 46277 (EN 50022)
Weight (kg)	0,272

Environmental characteristics

Protection class	IP 20
Relative humidity (without condensation)	5...95 %
Operating temperature	-20...+50 °C

Current measurement circuit

Installation category	CAT III 300 V
Nominal current (In)	... / 1A
Phase current measuring range	2...120% de In

Voltage measurement circuit

Installation category	CAT III 300 V
Voltage measuring range	5 ... 120 % Un
Nominal voltage	285V Ph-N, 480V Ph-Ph

Communication Network

Technology / Interface	Ethernet 10/100 Mbps

Standards

Electrical safety, Maximum height (m)	2000
Electrical safety, Installation category	CAT III 300 V
Electrical safety, Contamination level/class	Double-insulated electric shock protection class II (IEC 61010)

Creation date: 04/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.



eManager Pro Energy X2

Code: D302000080000

Standards	UNE EN 61010-1, UNE-EN 61000-6-2, UNE-EN 61000-6-4

Electrical safety

Insulation	3 kVac

Measurement accuracy

Reactive energy measurement (kvarh)	Class 2
Active energy measurement (kWh)	Class 1

Serial communication

Technology / Type	RS-232 (full-duplex) / RS-485 (half-duplex)Galvanic isolation

Wireless communication

Band	802.11 b/g/n (2.4 GHz.)
Technology / Interface	Wi-Fi

eManager Energy
IoT programmable controllers with integrated energy metering

CODE	TYPE	CPU	Memory	Communications	Power supply
eManager Energy					
D302000070000	eManager Pro Energy	ARM Cortex A7 800 MHz	512 MB | 8 GB eMMC	RS232/485 | Ethernet | Wi-Fi	85 ... 264 V~
D302000080000	eManager Pro Energy X2	ARM Cortex A7 800 MHz	512 MB | 8 GB eMMC	RS232/485 | Ethernet | Wi-Fi	85 ... 264 V~
D302200080000	eManager Pro 4G Energy X2	ARM Cortex A7 800 MHz	512 MB | 8 GB eMMC	RS232/485 | Ethernet | Wi-Fi | 4G EMEA	85 ... 264 V~

Creation date: 04/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.