eManager 2 Pro Dual Ethernet

eManager 2 Pro Dual Ethernet, ARM controller

Code: D3040000G0000

> Memory: 4 GB | 16 GB eMMC
> Módules: 4
> Communications: RS232/485 | CAN BUS | Ethernet x2 | Wi-Fi
> Power supply: 85 ... 264 V~
> CPU: ARM Cortex A53 Pro


Description

eManager 2 is a high-performance industrial OEM device designed with an embedded system based on Linux Yocto. Its flexible architecture makes it an ideal solution for automation, industrial IoT, and remote control applications.

The device integrates RS-232 and RS-485 serial communications, CAN FD bus, an Ethernet network interface, and Wi-Fi connectivity. It incorporates a TPM 2.0 security chip, which reinforces data protection and system integrity.

eManager 2 also includes a software suite that facilitates both device configuration and application development. This suite incorporates tools such as Node-RED, ChirpStack, and the TICK and MING stacks.

The device has access to an online package repository, which allows for the easy installation of additional components such as databases, VPN servers, and Docker containers, among others.researcher



Creation date: 04/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.

eManager 2 Pro Dual Ethernet

2nd generation programmable IoT controllers

Code: D3040000G0000

Specifications

AC power supply

Frequency	47 ... 63 Hz
Nominal voltage	85 ... 264 V~

DC power supply

Nominal voltage	120 ... 300 Vdc

Mechanical characteristics

Size (mm) width x height x depth	88 x 99.6 x 78.4 (mm)
Envelope	Polycarbonate UL94 - Self-extinguishing V8
Fastening	DIN rail
Weight (kg)	0,246

Environmental characteristics

Protection class	IP 30
Relative humidity (without condensation)	5...95 %

Voltage measurement circuit

Installation category	CAT III 300 V

Communication Network

Technology / Interface	Ethernet 10/100/1000 Mbps

Standards

Electrical safety, Maximum height (m)	2000
Electrical safety, Installation category	CAT III 300 V

Electrical safety

Insulation	3 kVac

Serial communication

Technology / Type	RS-232 (full-duplex) / RS-485 (half-duplex) / CAN-FD (semi-duplex) Galvanic isolation

Wireless communication

Band	802.11 a/b/g/n/ac (2.4 - 5 GHz.)
Technology / Interface	Wi-Fi

Creation date: 04/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.

eManager 2 Pro Dual Ethernet

2nd generation programmable IoT controllers

Code: D3040000G0000

eManager 2 Essential
2nd generation programmable IoT controllers

CODE	TYPE	Power supply	CPU	Communications	Memory	Digital inputs	N° relays	Analogue Inputs	Módules
eManager 2 Essential									
D20400.	eManager 2	85 ... 264 V~	ARM Cortex A53 Basic	RS232/485 | CAN BUS | Ethernet | Wi-Fi	1 GB | 8 GB eMMC	-	-	-	3
D20401.	eManager 2 (DC)	9...36 Vdc	ARM Cortex A53 Basic	RS232/485 | CAN BUS | Ethernet | Wi-Fi	1 GB | 8 GB eMMC	-	-	-	3
D20440.	eManager 2 NB-IoT & LTE-M	85 ... 264 V~	ARM Cortex A53 Basic	RS232/485 | CAN BUS | Ethernet | Wi-Fi | NB-IoT & LTE-M	1 GB | 8 GB eMMC	-	-	-	4
D20450.	eManager 2 4G	85 ... 264 V~	ARM Cortex A53 Basic	RS232/485 | CAN BUS | Ethernet | Wi-Fi | 4G	1 GB | 8 GB eMMC	-	-	-	4
D30400.	eManager 2 Pro	85 ... 264 V~	ARM Cortex A53 Pro	RS232/485 | CAN BUS | Ethernet | Wi-Fi	4 GB | 16 GB eMMC	-	-	-	3
D3040000G0000	eManager 2 Pro Dual Ethernet	85 ... 264 V~	ARM Cortex A53 Pro	RS232/485 | CAN BUS | Ethernet x2 | Wi-Fi	4 GB | 16 GB eMMC	-	-	-	4
D30450.	eManager 2 Pro 4G	85 ... 264 V~	ARM Cortex A53 Pro	RS232/485 | CAN BUS | Ethernet | Wi-Fi | 4G	4 GB | 16 GB eMMC	-	-	-	4
D3045000H0000	eManager 2 Pro 4G LoRaWAN BS	85 ... 264 V~	ARM Cortex A53 Pro	RS232/485 | CAN BUS | Ethernet | Wi-Fi | 4G | LoRaWAN	4 GB | 16 GB eMMC	-	-	-	5

Creation date: 04/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.

eManager 2 Pro Dual Ethernet

2nd generation programmable IoT controllers

Code: D3040000G0000

Dimensions

Creation date: 04/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.