



Line-M-4IO-R

Line-M-4IO-R, Expansion modules

Code: D73002.

- > Protocol: Modbus/RTU
- > Communications: Bus-Line
- > N° relays: 4
- > Digital inputs: 4
- > Mounting: DIN rail

Description

Module with 4 floating relay inputs and outputs.

The expansion modules of the Line range provide a simple way to extend the features of any version of line-EDS-Cloud, line-EDS-PS, or of the line-CVM-D32 network analyser.

They allow adding digital outputs and inputs, analogue inputs and outputs or any combination thereof, to the devices.

The modules are connected laterally and are detected automatically when the lateral connection is made, which greatly simplifies the installation and configuration of the modules.

Application

- Expansion of inputs/outputs from line-CVM-D32 or line-EDS network analysers.
- Management of up to 4 tariffs with activation of the different inputs to the module.
- Alarms can be programmed independently based on high/low values, hysteresis, timer on/off delays, normally open or closed rest state and interlocks.
- Track the status of components in the installation by using the status of the inputs to the module.



Line-M-4IO-R

Module with 4 relay inputs and outputs

Code: D73002.

Specifications

DC power supply

Consumption	max. 4 W
-------------	----------

Mechanical characteristics

Size (mm) width x height x depth	52.5 x 118 x 70 (mm)
Envelope	Self-extinguishing V0 plastic
Fastening	DIN rail (IEC 60715)
Weight (kg)	0,2

Environmental characteristics

Protection class	IP30, Front: IP40
Relative humidity (without condensation)	5 ... 95%
Storage temperature	-20 ... +70 °C
Operating temperature	-10 ... +50 °C

Voltage measurement circuit

Input impedance	3kΩ
-----------------	-----

Standards

Electrical safety, Maximum height (m)	2000
Electrical safety, Installation category	CAT III 300 V
Standards	UNE-EN 61010-1, UNE-EN 61000-6-2, UNE-EN 61000-6-4

User interface

LED	9 LED
-----	-------

Digital inputs

Input/output insulation	3,75 kV~
Quantity	4
Type	Optocoupler
Minimum signal width	10 ms

Digital relay outputs

Quantity	4
Type	Class A, high frequency current filtering
Maximum current	6 A ~
Maximum open contact voltage	250 V ~
Mechanical life	5 x 10 ⁶ Cycles
Maximum switching capacity	1500 VA



Line-M-4IO-R

Module with 4 relay inputs and outputs

Code: D73002.

Line-M-4IO-R

Expansion modules, Line series

CODE	TYPE	Protocol	Analogue Inputs	Transistor output	N° relays	Digital inputs	Analog output
Input/Output Modules							
M58E02.	Line-M-4IO-R	Modbus/RTU	-	-	4	4	-
D73002.	Line-M-4IO-R	Modbus/RTU	-	-	4	4	-

Bus-Line: RS-485 communication system, with side connector between modules





Line-M-4IO-R

Module with 4 relay inputs and outputs

Code: D73002.

Dimensions



Connections

