



## BAS-S154-200-308

BAS-S154-200-308, Indoor energy storage solution

Code: EB2583. DESCATALOGADO

- > Power (VA): 200 kVA
- > Rated capacity: 308 kWh
- > In (A): 290
- > Rated voltage (Vac): 400
- > Frequency (Hz): 50
- > Battery type: LFP
- > Protocol: Modbus TCP/IP

### Description

Modular indoor energy storage solution for connecting in parallel to the grid, LFP lithium technology Initial capacity of 154 kWh and 25 kVA of power (up to 616 kWh and 400 kVA).

- Standardized energy storage system, expandable up to 4 x 154 kWh in terms of exchanging both energy and power with the grid.
- All-in-one AC-coupled plug & play solution.
- Rated storage capacity of 154 kWh.
- From one to sixteen three-phase next-generation 4Q inverters of 25 kVA, for a total of 400 kVA.
- Lithium iron phosphate technology for maximum operational and fire prevention safety.
- FLEPS, systems to maximise fire safety
- All-in-one energy management system with cloud connection to monitor all the installed systems, and a reliable remote maintenance service.
- Easier maintenance thanks to plug-in modules (battery modules, battery management system, inverter).
- Additional UPS system for safe operation during power outages.
- Certified as per the VDE AR-N 4105/4110 standard.

### Application

- Electromobility
- Agriculture
- Industry
- Tertiary sector
- Reduction of spikes
- Emergency power
- Optimized self-supply
- Flexibility market
- Network services (voltage and frequency stabilization)



## BAS-S154-200-308

Indoor energy storage solution

Code: EB2583.

### Specifications

#### Battery specification

State of Health (SOH)	15 years > 5000 (90% DoD) (70% SOH @ EOL) > 6500 (70% DoD) > 8000 (50% DoD)
Useful life	15 years > 5000 (90% DoD) (70% SOH @ EOL) > 6500 (70% DoD) > 8000 (50% DoD)
Capacity	308 kWh
Performance-guarantee	10 years or 4000 cycles on the battery
Type	Lithium-Ionen (LiFePO4), prismatic

#### Electrical characteristics

Frequency	50 Hz
Surge protection (DSP)	Class 1 & 2
Nominal current In (A)	290
Power	200 kVA
Earthing system	TN-S, TN-C-S, TT
Nominal energy	154 kWh
Usable energy	277,2 kWh (90 % DoD)

#### Mechanical characteristics

Size (mm) width x height x depth	4000 x 2310 x 938 (mm)
Weight (kg)	2400

#### Environmental characteristics

Protection class	IP 11
Relative humidity (without condensation)	5 ... 95 %
Installation, location, position.	The room height min. 2.5m. A minimum width of 1.5 m must be maintained in order to allow access for maintenance work.
Ambient temperature	0 ... + 55 °C

#### Standards

Electrical safety, Maximum height (m)	2000
Standards	UNE-EN 61000-6-2, UNE-EN 61000-6-4, UNE-EN 61439-1, UNE-EN 61439-2, UNE-EN 62109-1, UNE-EN 62619, UN 38.3, VDE-AR-E 2510-50 (6.2.6), VDE-AR-N 4105, VDE-AR-N 4110, UNE-EN 50549-1, TOR Producer Typ A, 2014/53/EU (RED), 2014/30/EU (EMC), 2014/35/EU (LVD), 2006/66/E6 (Bat. directives), UNE 217002, UNE 206007-1, UNE 206006

#### BAS-S154



## BAS-S154-200-308

Indoor energy storage solution

Code: EB2583.

Modular energy storage system

CODE	TYPE	Power (VA)	Rated voltage (Vac)	Rated capacity	Battery type
EB2502.	BAS-S154-25	25 kVA	400 Vac	154 kWh	LFP
EB2583.	BAS-S154-200-308	200 kVA	400 Vac	308 kWh	LFP
EB25C3.	BAS-S154-300-308	300 kVA	400 Vac	308 kWh	LFP