TCP3RS

TCP3RS, Intelligent device concentrator for Autonomous management of parking guidance. Power supply: 230 Vac. Consumption: 2 VA. Communications RS-485 and Ethernet TCP-IP. DIN rail.,

Code: G50101.

Specifications

AC power supply

Consumption	4,6 ... 7,5 W
Frequency	47 ... 63 Hz.
Nominal voltage	85 ... 264 V~

DC power supply

Nominal voltage	120 ... 300 Vdc

Electrical characteristics

Cable: Connector type	RJ45

Mechanical characteristics

Material	UL94-V0 self-extinguishing plastic

Environmental characteristics

Protection class	IP20
Relative humidity (without condensation)	5 ... 95 %
Operating temperature	-10 ... +60 °C

Communication Network

Technology / Interface	Ethernet 10Base-T / 100Base-TX auto-detectable

Standards

Electrical safety, Maximum height (m)	200
Standards	IEC 60664, VDE 0110

Serial communication

Technology / Type	RS-485 / RS-232 three wires (A/S/B) (RX/GND/TX)

TCP3RS

CODE	TYPE
G50101.	TCP3RS

Creation date: 03/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.