PSC-240-48

PSC-240-48, Switching power supply. Power supply: 230 Vac. Output voltage: 48 Vdc. Power: 240 W. DIN rail.,

Code: G50201.

Specifications

AC power supply

Frequency	47 ... 63 Hz.
Nominal voltage	90 ... 264 V~

Electrical characteristics

Surge	56 ... 65 V; shutdown and automatic reset
Maximum transient current	105 ... 130 %; shutdown and automatic reset

Environmental characteristics

Relative humidity (without condensation)	20 ... 90 %
Storage temperature	-40 ... +85 °C
Operating temperature	-20 ... +70 °C
Operating temperature	-20 ... +70 °C

Mechanical characteristics

Thermal management	Free air convention

User interface

LED	DC ON: green LED; DC LOW: red LED

Standards

Standards	UL 508; UL 60950-1; EN 60950-1; EN 55011; EN 55022 (CISPR 22); EN 61204-3 Class B; EN 61000-3-2/-3; EN 61000-4-2/-3/-4/-5/-6/-8/-11; EN 55024; EN 61000-6-2 (EN 50082-2), heavy industrial level, criterion A

Power supply output

Voltage	48 ... 55 Vcc

PSC-240

CODE	TYPE
G50201.	PSC-240-48
G50202.	PSC-240-24

Creation date: 03/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.