

CVM-D41 DC V

CVM-D41 DC V, Digital multimeter DIN rail, 2 output relays

Code: M5663A0040000 **CONSULTAR DISPONIBILIDAD**

> Protocol: Modbus/RTU
> Módules: 6
> IP: 54
> Communications: RS-485
> Nº relays: 2
> Digital inputs: 2
> Analog output: 1 (0 ... 10V)
> System: DC (Shunt)
> Measurement Range (V): ± 150 / 300 /600 / 1000 / 1500 Vdc
> Measurement Range (A): 50 / 60 / 75 / 100 / 150 / 200 / 250 / 300 / 400 / 600 mV
> Parameters: V/A/kW/kWh dc
> Mounting: DIN Rail

Description

The **CVM-D41 DC** is a digital power analyzer for installing on a DIN rail. Its screens are operated using buttons to display different electrical parameters in a DC network of up to 1500 VDC, such as voltage, current, power and energy (A·h).

This analyzer has the following key features:

- DIN rail installation.
- DC voltage measurement up to 1500VDC CATIIII
- Shunt current measurement
- 2 digital inputs + 2 relay outputs + 1 analogue output (0/4...20 mA) or (0 / 2 ... 10 Vdc), depending on the model
- LED status indicator
- RS-485 communications (Modbus/RTU)
- Configuration via Power Studio SCADA

Application

Measurement and management of installations with a DC power supply:

- Industrial Applications
- Electric vehicle charging points
- Self-supply systems
- Solar photovoltaic Installations
- HVAC
- Industrial process control



CVM-D41 DC V

Digital instruments: Programmabled DC measurement Central

Code: M5663A0040000

Specifications

AC power supply

Installation category	CAT III 300V

DC power supply

Installation category	CAT III 300 V
Consumption	2.5 ... 4.5 W
Nominal voltage	20 ... 60 Vdc

Mechanical characteristics

Size (mm) width x height x depth	108 x 117.43 x 74 (mm)
Weight (kg)	0,7

Environmental characteristics

Relative humidity (without condensation)	≤ 93 %
Storage temperature	-25 ... +70 °C
Operating temperature	-25 ... +70 °C

Current measurement circuit

Installation category	CAT III 1500 V
Consumption	< 1 VA
Nominal current (In)	Shunt: 50 / 60 /75 / 100 / 150 / 200 / 250 / 300 / 400 / 600 mV
Allowable overload	1.2 In continuous (max.1500 Vdc)

Voltage measurement circuit

Installation category	CAT III 1500 V
Consumption	< 1 VA
Nominal voltage	± 150 / 300 / 600 / 1000 / 1500 Vdc
Maximum permanent measurement voltage	1.2 Un continuous

Standards

Electrical safety, Maximum height (m)	2000
Electrical safety, Contamination level/class	Pollution resistance 2
Standards	IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-8, IEC 61000-4-11, IEC 61010-1, IEC 61326-1, IEC 61010-2-030

User interface

Display type	LCD 5 digits

Digital inputs

Creation date: 04/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.



CVM-D41 DC V

Digital instruments: Programmabled DC measurement Central

Code: M5663A0040000

Input/output insulation	4000 V ~
Quantity	2
Type	Potential-free contact
Maximum short-circuit current	3.3 mA dc
Maximum open circuit voltage	17 V dc

Analogue outputs

Quantity	1
Linearity	0.5 %
Current mode: maximum load resistance	350 Ω
Voltage mode: nominal output range	0 / 2 ... 10 Vdc
Maximum internal voltage	17 V dc

Digital relay outputs

Quantity	2
Maximum current	2.5 A
Electrical life	1 x 10^5 (250 V~ / 5A)
Maximum switching capacity	625 VA

Measurement accuracy

Phase current measurement	Class 0.5
Active energy measurement (kWh)	Class 1
Active power measurement (kW)	Class 1
Phase voltage measurement	Class 0.5

Serial communication

Protocol	ModBus RTU
Technology / Type	RS-485

CVM-D41 DC

DC power analyzer

CODE	TYPE	System	Measurement Range (V)	Measurement Range (A)	N° relays	Digital inputs	Analog output	Módules	Protocol
Multimeter									
M56638.	CVM-D41 DC mA	DC (Shunt)	± 150 / 300 /600 / 1000 / 1500 Vdc	50 / 60 / 75 / 100 / 150 / 200 / 250 / 300 / 400 / 600 mV	2	2	1 (20 mA)	6	Modbus/RTU
M566380040000	CVM-D41 DC mA	DC (Shunt)	± 150 / 300 /600 / 1000 / 1500 Vdc	50 / 60 / 75 / 100 / 150 / 200 / 250 / 300 / 400 / 600 mV	2	2	1 (20 mA)	6	Modbus/RTU
M5663A.	CVM-D41 DC V	DC (Shunt)	± 150 / 300 /600 / 1000 / 1500 Vdc	50 / 60 / 75 / 100 / 150 / 200 / 250 / 300 / 400 / 600 mV	2	2	1 (0 ... 10V)	6	Modbus/RTU
M5663A0040000	CVM-D41 DC V	DC (Shunt)	± 150 / 300 /600 / 1000 / 1500 Vdc	50 / 60 / 75 / 100 / 150 / 200 / 250 / 300 / 400 / 600 mV	2	2	1 (0 ... 10V)	6	Modbus/RTU

Creation date: 04/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.



CVM-D41 DC V

Digital instruments: Programmabled DC measurement Central

Code: M5663A0040000

Creation date: 04/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.




CVM-D41 DC V


Digital instruments: Programmabled DC measurement Central

Code: M5663A0040000

Dimensions



Connections



Creation date: 04/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.