

MH-10/100u

MH-10/100u, Microohmmeter 10 / 100 A,

Code: P6071400A0000

Description

The digital micro-ohmmeter MH-100u is a microprocessor-controlled portable instrument designed to measure very low resistances with high accuracy with test currents from 1 mA to 100 A. The MH-100u micro-ohmmeter operates according to the 4 arms method (Kelvin bridge), thus avoiding the effect of the resistance of the injection cables. The test current can be selected by the operator and the indication is obtained by comparison with highly stable internal standards. The result is shown on an easy-to-read alphanumeric display. It also has a USB output to extract the data to media to manage measurements.

Application

Control of switchgear in MV Centres or Substations and electrical installations. Contact of circuit breakers, bus bars, windings of transformers and motors.

Creation date: 03/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.



MH-10/100u

Microohmmeter

Code: P6071400A0000

Specifications

Mechanical characteristics

Size (mm) width x height x depth	502 x 394 x 190 (mm)

MH
Microohmmeter

CODE	TYPE	Description
P6071100A0000	MH-10	Microohmmeter (Thomson Bridge)
P6071500A0000	MH-10r	Microohmmeter (Thomson Bridge)
P6071400A0000	MH-10/100u	Microohmmeter 10 / 100 A

Creation date: 03/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.