



CEM-C6-110

CEM-C6-110, single-phase energy meter, direct connection

Code: Q261120010000 DESCATALOGADO

- > Protocol: Modbus/RTU
- > Módulos: 1
- > Certification: IEC
- > Communications: RS-485
- > System: Single-phase
- > Measure: Direct
- > Measurement Range (V): 1 x 110
- > Measurement Range (A): 10 (100) A
- > Quadrants: 4

Description

CEM-C6 is a single-phase electrical energy meter that can measure up to 100 A, is capable of measuring energy in two directions and has Class 1 accuracy. In addition, the meter features a built-in RS-485 / Modbus RTU communication system.

Other features:

- Complies with the **IEC 62052-11** and **IEC 62053-21** standards (general and specific requirements of measuring units)
- Compact dimensions (1 DIN rail module, 18 mm)
- Backlit LCD display (6 digits) with a scrolling screen system used to display the electrical parameters (V, A, kW, kvar, kVA, kWh and $\cos \varphi$).

Application

- Measurement of the consumption of electricity in buildings, machinery or the tertiary sector.
- Control of consumption with a multi-tariff function, to measure the consumption of each period
- Energy consumption is reported to a remote system.



CEM-C6-110

Single-phase electrical energy meter, for assembly on DIN Rail

Code: Q261120010000

Specifications

AC power supply

Nominal voltage 110 V ~

Mechanical characteristics

Size (mm) width x height x depth 18 x 90 x 72 (mm)

Weight (kg) 0,1

Environmental characteristics

Relative humidity (without condensation) 95 %

Current measurement circuit

Nominal current (In) 10 A

Maximum current 100 A

Voltage measurement circuit

Nominal frequency 50 / 60 Hz.

Maximum input voltage consumption $\leq 8 \text{ VA}$, $\leq 0,4 \text{ Wh}$

User interface

LED 1000 imp / kWh (amplitude: 90 ms)

Keyboard 1 Keys

Display type LCD

Maximum value 99999,9 kWh

Measurement accuracy

Active energy measurement (kWh) Class 1 (IEC 62053-21)

Serial communication

Protocol Modbus RTU

Technology / Type RS-485

CEM-C6

Direct Single-phase energy meter with basic analyser parameters

CODE	TYPE	Protocol	Módulos	Certification	Communications	Measurement Range (V)	Measurement Range (A)	Quadrants	Transistor output	Digital inputs	Tariff
Q26112.	CEM-C6	Modbus/RTU	1	IEC	RS-485	1 x 230	10 (100) A	4			
Q26115.	CEM-C6-MID	Modbus/RTU	1	MID	RS-485	1 x 230	10 (100) A	2			
Q261120010000	CEM-C6-110	Modbus/RTU		IEC	RS-485	1 x 110	10 (100) A		-	-	-



CEM-C6-110

Single-phase electrical energy meter, for assembly on DIN Rail

Code: Q261120010000

Frequency: 50/60 Hz. Parameters: V, A, kW, kVA, kWh, cos phi



CEM-C6-110

Single-phase electrical energy meter, for assembly on DIN Rail

Code: Q261120010000

Dimensions

