,

Code:

Description

CIRWATT B is a multi-function digital single-phase meter, Class B in active energy and Class 2 in reactive energy. The meter complies with European legislation related to energy meters (MID) **EN 50470-1** and **EN 50470-3**, which approves the installation of these meters in any country of the European Union.
It includes PLC / PRIME (Power Line Carrier) Communications through power cable and an optical communications port. Both use **DLMS** protocol. In addition, it can display information in case of power loss just pressing the button, it can store up to 6 channels of energy registers with 3 months of hourly load profile and it can limit maximum power consumed by end-user, through an internal disconnection relay which can be remotely managed using PLC communications

Application

The main application of the **CIRWATT B** meter is the metering of active and reactive energy for billing purposes, whenever a meter with high performance features is required at an optimised cost. PLC communications can be used for the remote download of all data recorded by the meter through a **PLC-1000** concentrator or any other PRIME concentrator.
The circuit breaker integrated in the meter can be used to manage the supply remotely, opening/closing the circuit breaker and programming the hired power above a value that will activate the circuit breaker, opening it and reclosing it to guarantee the safety for the final user

Creation date: 04/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.



Code:

Specifications

AC power supply

Tolerance	80 % ... 115 % Un
Consumption	< 2 W; < 10 VA
Frequency	50 ... 60 Hz
Nominal voltage	110 ... 230 V (80 ... 115 %)

Mechanical characteristics

Size (mm) width x height x depth	172 x 206 x 67 (mm)
Envelope	DIN 43859
Weight (kg)	0,74

Environmental characteristics

Relative humidity (without condensation)	95 % max.
Storage temperature	-40 ... +85 °C
Operating temperature	-40 ... +70 °C

Voltage measurement circuit

Connection	Asymmetrical
Consumption	< 2 W; 10 VA
Nominal frequency	50 / 60 Hz
Nominal voltage	230 V

Current measurement circuit

Consumption	0,024 VA @ 10 A
Reference current (Iref)	10 A
Maximum current	60 A
Minimum current measurement	25 mA

Communication Network

Protocol	230 V

Battery specification

Performance-guarantee	> 20 years @ 30 °C
Type	Lithium

Optical communication interface

Hardware	IEC 62056-21
Protocol	DLMS
Type	Serial;bi-directional



Code:

User interface

Resolution of the display	up to 6 digits (9 mm)
Display type	LCD

Memory

Memory capacity	Data: non-volatile memory, Setup and events: serial-flash
Write time	90 days
Type	Serial flash

PLC

Hardware	CENELEC A
Protocol	DLMS / PRIME
Modulation system	OFDM with repeater system

Measurement accuracy

Reactive energy measurement (kvarh)	UNE-EN 62053-21 (Class 2)
Active energy measurement (kWh)	EN 50470 (Class B) IEC 62053-21 (Class 1)

Features / performance

Billing closures	12 locks per contract. Programable date and hour
Load curve	1 load curves, programmable integration time (1 ... 60 min)
Tariff programming	12 days 24 types of data 6 types of tariffs 30 public holidays

Clock

Source	Temperature compensated oscillator
Accuracy (EN 61038)	< 0,5 s/day
Type	Gregorian calendar

CIRWATT B II PRIME

Single-phase energy meters with PLC system (measuring, load profiling, multi configurable billing calendar)


CODE	TYPE	Communications	N° relays	Class (Active/Reactive)	Measure	Measurement Range (V)	Measurement Range (A)	Discon. relay	Hourly discrimination
CIRWATT B 200RCP									
QB3C0M10	212-ES4A-B0B17	PRIME	0	B (1) / 2	Direct	230	10 (60)	1	2.0DHA / 2.1DHA
QB3C0	212-ES4A-B0B17	PRIME	0	B / 2	Direct	230	10 (60)	1	-
QB3C0M11	212-ES4A-B0B17	PRIME	0	B (1) / 2	Direct	230	10 (60)	1	2.0A / 2.1A
QB3C3	212-ES4A-BFB-17	PRIME	1	B / 2	Direct	230	10 (60)	1	-
QB3C3M10	212-ES4A-BFB17	PRIME	1	B (1) / 2	Direct	230	10 (60)	1	2.0DHA / 2.1DHA
QB3C3M11	212-ES4A-BFB17	PRIME	1	B (1) / 2	Direct	230	10 (60)	1	2.0A / 2.1A

Creation date: 04/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.



Code:

Dimensions



Connections

