



CSB-M-50-440

CSB-M-50-440, Power capacitors with circuit breaker protection

Code: R2394K.

- > Cable section (mm²): 25
- > kvar (400 V): 42
- > kvar (440 V): 50
- > Cut off power: 10 kA
- > Aut.Switch (A): 100
- > Use voltage (V): 440
- > Type of protection: Circuit breaker

Description

The application of new technologies have allowed CIRCUTOR to reinvent the classic **CS** capacitor, manufactured for more than 35 years.

The spirit of innovation and proprietary technology used during the design of the new **CSB** capacitor have increased the working life of conventional prismatic capacitors by over 60%. This new series has improved all aspects of the previous models, offering our customers a capacitor that is longer lasting, safer and more cost-efficient.

Application

Its application is mainly based on the compensation of transformers and motors. In general, they are used for the compensation of installations with constant loads.



CSB-M-50-440

Three-phase power capacitor with circuitbreaker protection

Code: R2394K.

Specifications

AC power supply

Frequency	50 Hz
-----------	-------

Electrical characteristics

Permanent overload	1,3 In
Losses (W)	Dielectric: < 0,2 W / kvar Total: < 0,5 W / kvar
Discharge resistance	75 V / 3 min
Surge	10%
Tolerance C	± 10 %
Voltage	440 V
Insulation voltage, circuit	3 / 15 kV

Mechanical characteristics

Size (mm) width x height x depth	140 x 381 x 280 (mm)
Envelope	Treated and painted steel in RAL 3005 colour
Thermal management	Natural or forced according to cabinet design
Fastening	Vertical / Horizontal. Minimum distance between condensers 4 cm
Weight (kg)	9

Environmental characteristics

Protection class	IP 42 with terminal cover
Relative humidity (without condensation)	80%
Operating temperature	T° class D: Daily average: 45 °C, annual average: 35 °C, maximum: 55 °C, minimum: -25 °C

Standards

Electrical safety, Maximum height (m)	2000
Standards	IEC 60831-1, UNE-EN 60831-1

Features / performance

Components	CSB capacitor General three-pole circuit breaker protection
------------	---

Protection

Circuit breaker type	Dielectric regeneration Internal fuse Overpressure system Vermiculite
----------------------	---

CSB-M

Power capacitors with miniature circuit breaker protection, 50 Hz



CSB-M-50-440

Three-phase power capacitor with circuitbreaker protection

Code: R2394K.

CODE	TYPE	kvar (230 V)	Use voltage (V)	kvar (400 V)	kvar (440 V)
230 Vac, 50 Hz					
R23718.	CSB-M-5-230	5	230		
R2371A.	CSB-M-7,5-230	7,5	230		
R2371C.	CSB-M-10-230	10	230		
R2371D.	CSB-M-12,5-230	12,5	230		
R2371E.	CSB-M-15-230	15	230		
R2371F.	CSB-M-20-230	20	230		
R2371G.	CSB-M-25-230	25	230		
R2371H.	CSB-M-30-230	30	230		
440 Vac, 50 Hz					
R23948.	CSB-M-5-440		440	4	5
R2394A.	CSB-M-7,5-440		440	6	7,5
R2394C.	CSB-M-10-440		440	8	10
R2394D.	CSB-M-12,5-440		440	10	12,5
R2394E.	CSB-M-15-440		440	12,5	15
R2394F.	CSB-M-20-440		440	17	20
R2394G.	CSB-M-25-440		440	21	25
R2394H.	CSB-M-30-440		440	25	30
R2394J.	CSB-M-37,5-440		440	31	37,5
R2394K.	CSB-M-50-440		440	42	50
R2394L.	CSB-M-60-440		440	50	60
R2394M.	CSB-M-75-440		440	66	75



CSB-M-50-440

Three-phase power capacitor with circuitbreaker protection

Code: R2394K.

Dimensions

