



URBAN-WB T22 Gen3

URBAN-WB T22 Gen3, Indoor charging wall box

Code: V20693. **CONSULTAR DISPONIBILIDAD**

- > Communications: Ethernet|Wi-Fi
- > Output type: 400 Vca - 32 A - 22 kW
- > Connector type: Type 2 socket
- > Grid type: Three-phase
- > Charge mode: 3
- > No. Sockets: 2
- > Earth leakage protection: RCD Type A (30 mA)

Description

URBAN-WB WB charging posts have been designed as a robust solution for publicly accessible environments, and are capable of withstanding a wide range of environmental conditions and possible acts of vandalism, while providing simple installation and maintenance for operators.

URBAN-WB devices facilitate charging tasks for all kinds of EV users, incorporating all the electrical protections necessary to guarantee safety inside an aluminium metal body. They can use type-1 and type-2 cables and type-2 plugs, enabling recharging in Mode 3.

The **URBAN-WB** series is designed for complex applications where the highest standards of performance are required, with remote management and monitoring or integration into management platforms based on the 1.5 or 1.6 OCPP protocol.

Application

URBAN WB charging posts are especially suitable for all types of outdoor parking. Applications range from public squares, department stores, airports, vehicle sales and rental companies, private car parks, etc.



URBAN-WB T22 Gen3

Smart charging devices

Code: V20693.

Specifications

AC power supply

Input intensity	64 A
Frequency	50/60 Hz
Type of network	3F + N + PE
Nominal voltage	400 V ~ (± 10%)

Electrical characteristics

Overcurrent protection	PIA 40 A (curve C)
Cable: Connector type	Type 2 socket
Charging mode	Mode 3 (IEC 61851-1)
No. of charges	2
Voltage	400 V ~ (± 10 %)

Mechanical characteristics

Size (mm) width x height x depth	382 x 928 x 222 (mm)
Envelope	Aluminio y ABS
Fastening	Pared (Mural)
Weight (kg)	25

Environmental characteristics

Protection class	IP 54 / IK10
Relative humidity (without condensation)	5 ... 95 %
Storage temperature	-20 ... +60 °C
Operating temperature	-5 ... +50 °C

Communication Network

Protocol	OCPP 1.6J / 2.0 HW Ready
Technology / Interface	Ethernet 10/100 Base TX (TCP/IP)

User interface

RFID (Radio-Frequency Identification)	ISO/IEC 14443 A/B, FELICA, ISO/IEC 15693 / ICODE
LED	Indicador de carga en color RGB
Display type	LCD Multi-idiomas

Standards

Standards	IEC 61851-1, IEC 61851-21-1, IEC 62196-1, IEC 62196-2, Directiva 2014/35/UE, LVD; 2014/30/UE, EMC
-----------	---

Features / performance



URBAN-WB T22 Gen3

Smart charging devices

Code: V20693.

Energy measurement	MID Class 1 Meter, EN 50470-3
Optional	• 4G / GPRS Modem • Protección diferencial Tipo A con reconexión automática • Protección diferencial Tipo B • Protección diferencial Tipo B con reconexión automática • Kit de baja temperatura (-30 °C)

Protection

Element	- MCB (40A) Curva de disparo "C" por toma. - RCD Tipo A (30 mA) por toma.
---------	---

Output 1

Maximum current	32 A
Maximum power	22 kW
Voltage range	400 Vca
Connector type	Base Tipo 2
Network type	Trifásica (CA)

Output 2

Maximum current	32 A
Maximum power	22 kW
Voltage range	400 Vca
Connector type	Base Tipo 2
Network type	Trifásica (CA)

Wireless communication

Technology / Interface	Wi-Fi
------------------------	-------

URBAN-WB

Intelligent double socket charging boxes

CODE	TYPE	Output type	Connector type	Grid type
URBAN-WB				
V20622.	URBAN-WB M22	230 Vca - 32 A - 7,4 kW	Type 2 socket	Single-phase
V2062200000C2	URBAN-WB M22	230 Vca - 32 A - 7,4 kW	Type 2 socket	Single-phase
V2062A.	URBAN-WB M22-C2	230 Vac- 32 A - 7,4 kW	Cable Type 2	Single-phase
V2062A00000C2	URBAN-WB M22-C2	230 Vac- 32 A - 7,4 kW	Cable Type 2	Single-phase
V20623.	URBAN-WB T22	400 Vca - 32 A - 22 kW	Type 2 socket	Three-phase
V20693.	URBAN-WB T22 Gen3	400 Vca - 32 A - 22 kW	Type 2 socket	Three-phase
V20625.	URBAN-WB M22-C1	230 Vca - 32 A - 7,4 kW	Type 1 cable	Single-phase
V20626.	URBAN-WB T22-C2	400 Vca - 32 A - 22 kW	Type 2 cable	Three-phase
V20696.	URBAN-WB T22-C2 Gen3	400 Vca - 32 A - 22 kW	Type 2 cable	Three-phase



URBAN-WB T22 Gen3

Smart charging devices

Code: V20693.

Independent, 30-mA, type-A earth leakage protection and circuit breaker protection per plug, MID Integrated energy measurement, RFID reader for identification and charging activation - ISO 14443 A/B, Data storage, Ethernet communications, 4G communications (optional), OCPP 1.5/1.6 communications protocol, Weight: 55 kg, Aluminium housing IP54-IP65, Dimensions 928x450x290 mm. 4-m cable length (depending on model).




URBAN-WB T22 Gen3

Smart charging devices

Code: V20693.

Dimensions



Connections

