



ePark M-S2 Gen4

ePark M-S2 Gen4, Car park boxes

Code: V27540.

- > Communications: Ethernet | WiFi
- > Output type: 230 Vac- 32 A - 7,4 kW
- > Connector type: Type 2 socket
- > Grid type: Single-phase
- > Charge mode: 3
- > No. Sockets: 1
- > Earth leakage protection: 6 mA CC

Description

With a modern and minimalist design, the **ePark** range is the best smart charging option for multi-user car parks in residential blocks, work places and car parks. This range has several dual-charger models that allow simultaneous charging of two vehicles with both single-phase and three-phase lines, making it the ideal solution for installing charging stations in multi-user car parks and adapting the facilities to the new needs of electric cars.

The minimalist interface, consisting of a display and LEDs to indicate the charging status, provides an intuitive and friendly user experience. This range is compatible with our dynamic power management system (DLM) to regulate the charge without exceeding the contracted power. The device also has an OCPP communications protocol for easy integration with management platforms.

Application

The **ePark** range is designed to manage multiple users in covered car parks who need to recharge their electric vehicles, such as parking areas in residential blocks or condominiums, work places and public car parks.



ePark M-S2 Gen4

Electric vehicle charging device

Code: V27540.

Specifications

AC power supply

Input intensity	32A
Frequency	50/60 Hz
Type of network	1F + N + PE
Nominal voltage	230 V ~ ($\pm 10\%$)

Electrical characteristics

Charging mode	Mode 3 (IEC 61851-1)
No. of charges	1
Voltage	230 V ~ ($\pm 10\%$)

Mechanical characteristics

Size (mm) width x height x depth	335 x 315 x 179.7 (mm)
Envelope	PC + GF 10%
Fastening	Wall fixing with 3 screws
Weight (kg)	7,3

Environmental characteristics

Protection class	IP 54 / IK 10
Relative humidity (without condensation)	5 ... 95 %
Storage temperature	-20 ... +60 °C
Operating temperature	-5 ... +50 °C

Communication Network

Protocol	OCPP 1.6J / 2.0 HW Ready
Technology / Interface	Ethernet 10/100 Base TX (TCP/IP)

User interface

RFID (Radio-Frequency Identification)	ISO / IEC 14443 A/B / MIFARE Classic / DESFire EV1 / ISO 18092 / ECMA - 340
LED	RGB colour charge indicator
Display type	3.5" screen

Standards

Standards	IEC 61851-1:2017; IEC 61851-21-2:2018; IEC 62196-1; IEC 62196-2; Directives: 2014/53/EU, 2014/30/EU, 2014/35/EU; RoHS 2011/65/EU compliant; 4G Modem complies with CE/RED
-----------	---

Features / performance

Energy measurement	MID Class B meter, EN 50470-3
--------------------	-------------------------------



ePark M-S2 Gen4

Electric vehicle charging device

Code: V27540.

Optional

- 4G / GPRS Modem
- Low temperature kit (-30 °C)

Protection

Element	Built-in residual current protection 6 mA DC per socket.
---------	--

Output 1

Maximum current	32 A
Maximum power	7,4 kW
Voltage range	230 Vca
Connector type	Type 2 base
Network type	Single-phase (CA)

Wireless communication

Band	2,4 GHz
Technology / Interface	Wi-Fi

ePark

Intelligent charging boxes

CODE	TYPE	Output type	No. Sockets	Connector type	Grid type	Communications	Earth leakage protection	Charge mode
V27540.	ePark M-S2 Gen4	230 Vac- 32 A - 7,4 kW	1	Type 2 socket	Single-phase	Ethernet WiFi	6 mA CC	3
V27520.	ePark M-C2 Gen4	230 Vac- 32 A - 7,4 kW	1	Type 2 cable	Single-phase	Ethernet WiFi	6 mA CC	3
V27522.	ePark M-2C2 Gen4	230 Vac- 32 A - 7,4 kW	2	Type 2 cable	Single-phase	Ethernet WiFi	6 mA CC	3
V27544.	ePark M-2S2 Gen4	230 Vac- 32 A - 7,4 kW	2	Type 2 socket	Single-phase	Ethernet WiFi	6 mA CC	
V27640.	ePark T-S2 Gen4	400 Vac - 32 A - 22 kW	1	Type 2 socket	Three-phase	Ethernet WiFi	6 mA CC	3
V27620.	ePark T-C2 Gen4	400 Vac - 32 A - 22 kW	1	Type 2 cable	Three-phase	Ethernet WiFi	6 mA CC	
V27622.	ePark T-2C2 Gen4	400 Vac - 32 A - 22 kW	2	Type 2 cable	Three-phase	Ethernet WiFi	6 mA CC	3
V27644.	ePark T-2S2 Gen4	400 Vac - 32 A - 22 kW	2	Type 2 cable	Three-phase	Ethernet WiFi	6 mA CC	3
V27100.	ePark	230 Vac- 32 A - 7,4 kW	2	Type 2 socket	Single-phase	Ethernet		3
V27240.	ePark M-S2	230 Vac- 32 A - 7,4 kW	1	Type 2 socket	Single-phase	Ethernet		3
V2724000000C2	ePark M-S2	230 Vac- 32 A - 7,4 kW	1	Type 2 socket	Single-phase	Ethernet		3
V27220.	ePark M-C2	230 Vac- 32 A - 7,4 kW	1	Type 2 cable	Single-phase	Ethernet		3
V2722000000C2	ePark M-C2	230 Vac- 32 A - 7,4 kW	1	Type 2 cable	Single-phase	Ethernet		3
V27222.	ePark M-2C2	230 Vac- 32 A - 7,4 kW	2	Type 2 cable	Single-phase	Ethernet		3
V27211.	ePark M-2C1	230 Vac- 32 A - 7,4 kW	2	Type 1 cable	Single-phase	Ethernet		3
V2724400000C2	ePark M-2S2	230 Vac- 32 A - 7,4 kW	2	Type 2 socket	Single-phase	Ethernet		3
V27244.	ePark M-2S2	230 Vac- 32 A - 7,4 kW	2	Type 2 socket	Single-phase	Ethernet		3
V2722200000C2	ePark M-2C2	230 Vac- 32 A - 7,4 kW	2	Type 2 cable	Single-phase	Ethernet		3
V27440.	ePark T-S2	400 Vac - 32 A - 22 kW	1	Type 2 socket	Three-phase	Ethernet		3



ePark M-S2 Gen4

Electric vehicle charging device

Code: V27540.

CODE	TYPE	Output type	No. Sockets	Connector type	Grid type	Communications	Earth leakage protection	Charge mode
V27344.	ePark T-2S2 Gen3	400 Vac - 32 A - 22 kW	2	Type 2 socket	Three-phase	Ethernet WiFi	6 mA dc	3
V27420.	ePark T-C2	400 Vac - 32 A - 22 kW	1	Type 2 cable	Three-phase	Ethernet		3
V27322.	ePark T-2C2 Gen3	400 Vac - 32 A - 22 kW	2	Type 2 cable	Three-phase	Ethernet WiFi	6 mA dc	3
V27444.	ePark T-2S2	400 Vac - 32 A - 22 kW	2	Type 2 socket	Three-phase	Ethernet Wi-Fi		3
V27422.	ePark T-2C2	400 Vac - 32 A - 22 kW	2	Type 2 cable	Three-phase	Ethernet Wi-Fi		3
V274400000C2	ePark T-S2	400 Vac - 32 A - 22 kW	1	Type 2 socket	Three-phase	Ethernet		3
V274200000C2	ePark T-C2	400 Vac - 32 A - 22 kW	1	Type 2 cable	Three-phase	Ethernet		3

Integrated MID-certified energy measurement, RFID reader for authentication and charge activation - ISO 14443 A/B, data storage, Ethernet communications, 4G communications (optional), OCPP 1.6J / 2.0 HW communications protocol, weight: 4 kg, PC + GF 10% - IP54 - IK10 casing, dimensions 200x335x315 mm. 5-m cable length, cable holder included (depending on model).



ePark M-S2 Gen4

Electric vehicle charging device

Code: V27540.

Dimensions

