



DHB-424

DHB-424, Instrumentação digital: processo, temperatura e resistência

Código: M22028. DESCATALOGADO

- > Comunicações: RS-485
- > N° relés: 4
- > Saida analógica: 1 (0/4...20 mA) | 1(0...10V)
- > Medida: Pt100/500/1000 Termopar J,K,N,E,R,S, ± 20 mA, ± 10 V, 60 mV
- > Parâmetro: Processo / Resistencia / Temperatura
- > Fixação: Painei

Descrição

Panel mounted digital devices designed to display on-screen the value of a electrical variable measured or proportional value of a process signal, depending on the model. Essential for regulation purposes, programming the analogue output available in some models, and for control purposes, if the relay outputs are used as alarms.

DHB units are fully programmable and the following can be programmed: scale, transformation ratios, alarm setpoints to activate relays, communications, colour of the numbers displayed on screen, etc. Depending on the model, you can measure the electrical parameters of a single-phase installation such as voltage, current, frequency, power, $\cos \phi$, etc., the direct voltage or current of an installation, impulses, frequency, circular speed, periods, time, temperature and also other voltage and current process variables. AC models calculate the true root mean square measure (TRMS).

The models include the following common features:

- o IP 65 front panel
- o High measurement accuracy
- o Programmable measurement input
- o Delay and latching alarms
- o 24 Vdc output for supply external transducers (DHB 1xx and DHB 4xx models)
- o Galvanic insulation between external circuits
- o Adjustment of non-linear equations with 21 straight points (2 in the DHB 3xx model).
- o Change in colour of the display depending on the value shown.
- o Maximum and minimum values
- o Clock with current time
- o Self-configurable decimal point
- o Compatible with Power Studio (model with communications)
- o Installation on 96 x 48 mm panel

Aplicativo

These digital instruments have multiple applications. Thanks to their very bright 5-digit and 3-colour screen, you can simply view a numerical value and an alarm or prealarm status of a measured variable. Depending on the model selected, displayed on-screen are the electrical parameters of a single-phase installation as a power analyzer (voltage, current, power, frequency, etc.).

Other models allow to visualize the value of an analogue signal, show impulses received through an input, temperature, time, circular speed and many other variables that depends on the device and the configuration. The indicators also let you operate any external element, using the panel unit outputs as alarms depending on the value of a variable or as a transducer of the measured variable to an analogue signal, which is subsequently sent to another unit, such as a PLC.

Apart from displaying the values, units with communications also allow you to send data via the RS-485 communication bus for software or PLC integration.



DHB-424

Instrumentação digitais

Código: M22028.

Especificações

Características mecânicas

Tamanho (mm) larg. x alt. x prof.	96 x 48 x 93 (mm)
Envolvente	Plástico V0 autoextinguible
Peso (kg)	0,3

Características ambientais

Grau de proteção	IP 65 (Frontal), IP 10 (traseira)
Humidade relativa (sem condensação)	25...95 %
Temperatura de armazenamento	-33...+70 °C
Temperatura de trabalho	-25...+55 °C

Normas

Segurança Elétrica, Altitude máxima (m)	2000
---	------

Interface do utilizador

LED	7
Teclado	4 teclas
Tipo de visor	7 segmentos (5 dígitos) LED

DHB

Instrumento digital

CÓDIGO	MODELO N° relés	Medida	Parâmetro	Comunicações	Saída analógica
M22021.	DHB-102 1	imp., Hz.	Impulsos, frequência, velocidade circular, períodos, tempo, encoder		
M22022.	DHB-124 3	imp., Hz.	Impulsos, frequência, velocidade circular, períodos, tempo, encoder	RS-485	1 (0/4...20 mA) 1(0...10V)
M22023.	DHB-2022	± 100...500 Vcc ± 1/5 Acc	Voltímetro ou amperímetro ± 100...500 Vcc ± 1/5 Acc		
M22024.	DHB-224 4	± 100...500 Vcc ± 1/5 Acc	Voltímetro ou amperímetro ± 100...500 Vcc ± 1/5 Acc	RS-485	1
M22025.	DHB-3022	± 100/400 Vca ± 1/5 Aca	Analizador monofásico		
M22026.	DHB-324 4	± 100/400 Vca ± 1/5 Aca	Analizador monofásico	RS-485	1 (0/4...20 mA) 1(0...10V)
M22027.	DHB-4022	Pt100/500/1000 Termopar J,K,N,E,R,S, ±20 mA, ±10 V, 60 mV	Proceso / Resistencia / Temperatura		
M22028.	DHB-424 4	Pt100/500/1000 Termopar J,K,N,E,R,S, ±20 mA, ±10 V, 60 mV	Proceso / Resistencia / Temperatura	RS-485	1 (0/4...20 mA) 1(0...10V)




DHB-424

Instrumentação digitais

Código: M22028.

Dimensões



Conexões

